



Product Name: Cyprus Midi
Product Code: MKPL-5
Model No: 15000155

Product Specification / Ürün Özellikleri

Cyprus Midi

Installation Type : Pole Mounted / Surface Mounted

Body and Heatsink : Aluminium Injection Body and aluminium injection driver caps

Body and Heatsink : Aluminium Injection Body and aluminium injection driver caps

Glass Type : Tempered Glass

Lens : PMMA

Body Color : Electrostatic Powder Coating - RAL 7016 Standard

Led Type: SMD Led

Led Brands : Seoul / Osram

Driver Brands : Inventronics / Meanwell

Dimming Options : StepDIM / AstroDIM / Mains DIM / DALI / 0-10V/ PWM

Protection Type : IP65 / IK08 (Glass) / IK10 (Body)

Surge Protection : Internal (Driver) 6 - 8 - 10 kV / External 10 - 20 kV (Optional)

Product Dimensions : H:60mm W:380mm L:430mm

Screws : Stainless steel

Cyprus Midi

Montaj Tipi : Direğe Monte / Yüzeğe Monte

Gövde ve Soğutucu : Alüminyum Enjeksiyon Gövde ve alüminyum enjeksiyon sürücü kapağı

Gövde ve Soğutucu : Alüminyum Enjeksiyon Gövde ve alüminyum enjeksiyon sürücü kapağı

Cam Çeşidi : Tempered Glass

Lens : PMMA

Gövde Rengi : Elektrostatik Toz Boya - RAL 7016 Standart

Led Tipi: SMD Led

Led Markaları : Seoul / Osram

Sürücü Markaları : Inventronics / Meanwell /

Dim Opsiyonları : StepDIM / AstroDIM / Mains DIM / DALI / 0-10V/ PWM

Koruma Sınıfı : IP65 / IK08 (Cam) / IK10 (Gövde)

Parafudr : Dahili (Sürücü) 6 - 8 - 10 kV / Harici 10 - 20 kV (Opsiyonel)

Ürün Ölçüleri : Y:60mm G:380mm U:420mm

Vidalar : Paslanmaz çelik

-Long life due to thermal design cooling block

-Tempered / polycarbonate glass with pressure and heat resistance feature

-Solid aluminum injection-molded body with high level of heat transmittance

-Stainless assembly accessories and screws

-User-friendly socket system

-Silicon cable, resistant to internal and external temperature factors, and insulated rubber cabling

-Electrostatic paint with different available colours, which is resistant to atmospheric conditions and- whose surface treatment is completed



| | 3000K Lumen | 4000K Lumen | 5000K Lumen | Watt | CRI |
|---------------|--------------------|--------------------|--------------------|-------------|------------|
| Seoul / Osram | 17000 lm | 18000 lm | 19000 lm | 150 Watt | >82 |
| Seoul / Osram | 23000 lm | 24000 lm | 25000 lm | 200 Watt | >82 |

* Please check website for lens options.